



VAN BI ĐỒNG NỐI REN KITZ SZA

TÊN SẢN PHẨM

NHÃN HIỆU

Model

Kết Nối

Thân Van

Nắp Van

Ty Van

Bi Van

Đệm Kín

Kích Thước

Tình Trạng

Đơn Giá

VAN BI ĐỒNG NỐI REN

KITZ

Fig. SZA

Nối ren BSPT

Đồng / Brass

Đồng / Brass

Đồng / Brass

Đồng / Brass

PTFE

DN8 → DN100 (1/4" → 4")

Hàng có sẵn, mới 100%


Xin liên hệ

TYPE 600 BRASS BALL VALVE, FULL PORT

Bolted body and cap, Blowout-proof stem,
Double O-ring stem seals,
Threaded ends to ASME B1.20.1 or
solder joint ends

W.O.G. non-shock 4.14 MPa (600 psi)*, W.O.G. 150°C 1.03 MPa (150 psi)

*Size 4: W.O.G. non-shock 2.76 MPa (400 psi), W.O.G. 150°C 0.69 MPa (100 psi)

**Materials**

Parts	Material
Body	Brass/Bronze*
Body cap	Brass/Bronze*
Stem	Brass: Nickel plated
Ball	Brass: Tin-Nickel plated (Size 1/4 to 3) Brass: Nickel-chrome plated (Size 4)
Ball seat	PTFE
O-ring	FKM

*Size 4 only

Solder joint end valves should not be used in service where the temperature of the line fluid is higher than the softening point of the solder.

Fig. AKSZA

Fig. CSZA

• Threaded end to ASME B1.20.1 • Solder joint to ASME B16.18

Approvals
(up to 2)



*AKSZA only

Dimensions


Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
mm												
L	42	42	53	60	72	84	92	110	138	167	193	
L1 Solder			46	54	73	88	100	115	140	164	187	
H	37	37	40	43	50	55	65	72	100	112	131	
D	70	70	80	80	110	110	150	150	200	300	300	

TYPE 600 BRASS BALL VALVE, FULL PORT

Bolted body and cap, Blowout-proof stem,
Double O-ring stem seals,
Threaded ends to BS21

W.O.G. non-shock 4.14 MPa (600 psi), W.O.G. 150°C 1.03 MPa (150 psi)

*Size 4: W.O.G. non-shock 2.76 MPa (400 psi), W.O.G. 150°C 0.69 MPa (100 psi)

**Materials**

Parts	Material
Body	Brass/Bronze*
Body cap	Brass/Bronze*
Stem	Brass: Nickel plated
Ball	Brass: Chrome free plated (Size 1/4 to 3) Brass: Nickel-chrome plated (Size 4)
Ball seat	PTFE
O-ring	FKM

*Size 4 only

Dimensions

Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
mm												
L	42	42	53	60	72	84	92	110	138	167	193	
H	37	37	40	43	50	55	65	72	101	113	131	
D	70	70	80	80	110	110	150	150	200	300	300	


Fig. SZA

• Threaded end to BS21

TYPE 600 BRASS BALL VALVE, FULL PORT

Bolted body and cap, Blowout-proof stem,
Double O-ring stem seals,
Threaded ends to ASME B1.20.1 or
solder joint ends

W.O.G. non-shock 4.14 MPa (600 psi), W.O.G. 150°C 1.03 MPa (150 psi)

**Materials**

Parts	Material
Body	Brass
Body cap	Brass
Stem	Brass: Nickel plated
Ball	Brass: Tin-Nickel plated
Ball seat	PTFE
O-ring	FKM



Solder joint end valves should not be used in service where the temperature of the line fluid is higher than the softening point of the solder.

Fig. AKSZAW

Fig. CSZAW

• Threaded end to ASME B1.20.1 • Solder joint to ASME B16.18

Approvals
(up to 2)



*AKSZAW only

Dimensions

Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2
mm									
L	42	42	53	60	72	84	92	110	
L1 Solder			46	54	73	88	100	115	140
H	35	35	41	45	54	59	75	82	
D	55	55	70	70	100	100	130	130	

Sản phẩm khác



—

[VAN BƯỚC KITZ G-PN10ZJUE](#)

[Xem thêm VAN BƯỚC KITZ G-PN10ZJUE](#)



—

[VAN BƯỚC KITZ PN10ZJUE](#)

[Xem thêm VAN BUỒM KITZ PN10ZJUE](#)



—

[VAN 1 CHIỀU KITZ 10SFBF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SFBF](#)



—

[VAN 1 CHIỀU KITZ 10SF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SE](#)



—

[VAN 1 CHIỀU KITZ 150SCOS](#)

[Xem thêm VAN 1 CHIỀU KITZ 150SCOS](#)



—

[VAN BI KITZ 150SCTDZ](#)

[Xem thêm VAN BI KITZ 150SCTDZ](#)

