



VAN CẦU HƠI ĐỒNG NỐI REN 100PSI KITZ A

TÊN SẢN PHẨM

NHÃN HIỆU

Model

Xuất Xứ

Thân Van

Nắp Van

Ty Van

Đĩa Van

Đệm Kín

Kích Thước

Áp Lực

Tình Trạng

Đơn Giá

VAN HƠI ĐỒNG NỐI REN

KITZ

Fig. A

Nhật, Thái

Đồng / Bronze

Đồng / Bronze

Đồng / Brass

Đồng / Bronze

Than chì

DN8 → DN100 (1/4" → 4")

Class 100

Hàng có sẵn, mới 100%

Xin liên hệ

CLASS 100 BRONZE GLOBE VALVEScrewed bonnet, Rising stem,
Threaded ends to BS21 (JIS B0203) or NPT

W.O.G. non-shock 1.03 MPa (150 psi), Saturated steam pressure 0.7 MPa (100 psi)


**Fig. A***

• Threaded end to BS21 (JIS B0203)

Fig. AKA

• Threaded end to ASME B1.20.1

*Taper pipe threads for connection shall refer to JIS B0203 standards, while the length of useful threads and the positions of gauge planes are built on KITZ standard.

**Materials**

Parts	Material
Body	Bronze
Bonnet	Brass/Bronze*
Stem	Dezincification Resistant Brass
Disc	Bronze
Gland packing	Aramid Fibers Graphite

*Size 4 only

⚠ Do not use for flammable gas or toxic gas.

Dimensions

Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	mm	8	10	15	20	25	32	40	50	65	80	100
L		40	42	48	53	63	73	81	94	115	131	171
H valve open		66	67	69	80	94	104	127	147	179	200	250
D		50	50	55	60	70	80	90	100	115	135	180

CLASS 100 BRONZE GLOBE VALVEScrewed bonnet, Rising stem, Soft seated disc,
Threaded ends to BS21 (JIS B0203)

W.O.G. non-shock 0.86 MPa (125 psi)


**Fig. Q***

• Rubber disc

**Fig. QA***

• PTFE disc (for oil service)

*Taper pipe threads for connection shall refer to JIS B0203 standards, while the length of useful threads and the positions of gauge planes are built on KITZ standard.

**Materials**

Parts	Material
Body	Bronze
Bonnet	Brass
Stem	Dezincification Resistant Brass
Disc	Urethane rubber/PTFE
Gland packing	Aramid Fibers Graphite

⚠ Do not use for flammable gas or toxic gas.

Dimensions

Nominal Size	inch	1/2	3/4	1	1 1/4	1 1/2	2
	mm	15	20	25	32	40	50
L		44	50	63	73	81	94
H valve open		70	73	86	108	132	150
D		50	55	60	80	90	100

*Size 1 1/2 & larger = QA only

CLASS 150 BRONZE GLOBE VALVEScrewed bonnet, Rising stem,
Threaded ends to BS21 (JIS B0203) or NPT


W.O.G. non-shock 2.07 MPa (300 psi), Saturated steam pressure 1.03 MPa (150 psi)

**Fig. C**

• Threaded end to BS21 (JIS B0203)

Fig. AKC

• Threaded end to ASME B1.20.1

**Materials**

Parts	Material
Body	Bronze
Bonnet	Brass/Bronze*
Stem	Dezincification Resistant Brass
Disc	Bronze
Gland packing	Aramid Fibers Graphite

*Size 3 only

⚠ Do not use for flammable gas or toxic gas.

Dimensions

Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
	mm	8	10	15	20	25	32	40	50	65	80
L		44	44	53	65	77	85	100	119	139	158
H valve open		66	68	79	93	104	127	145	174	199	215
D		50	50	60	70	80	90	100	115	135	155

Sản phẩm khác



—

[VAN BƯỚC KITZ G-PN10ZJUE](#)

[Xem thêm VAN BƯỚC KITZ G-PN10ZJUE](#)



—

[VAN BƯỚC KITZ PN10ZJUE](#)

[Xem thêm VAN BUỒM KITZ PN10ZJUE](#)



—

[VAN 1 CHIỀU KITZ 10SFBF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SFBF](#)



—

[VAN 1 CHIỀU KITZ 10SF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SE](#)



—

[VAN 1 CHIỀU KITZ 150SCOS](#)

[Xem thêm VAN 1 CHIỀU KITZ 150SCOS](#)



—

[VAN BI KITZ 150SCTDZ](#)

[Xem thêm VAN BI KITZ 150SCTDZ](#)

