



VAN CỬA ĐỒNG NỐI REN KITZ FH

TÊN SẢN PHẨM

NHÃN HIỆU

Model

Xuất Xứ

Thân Van

Nắp Van

Ty Van

Đĩa Van

Đệm Kín

Kích Thước

Áp Lực

Tình Trạng

Đơn Giá

VAN CỬA ĐỒNG NỐI REN
KITZ

Fig. FH

Nhật, Thái

Đồng / Brass

Đồng / Brass

Đồng / Brass

Đồng / Brass

Than chì

DN8 → DN80 (1/4" → 3")

Class 125

Hàng có sẵn, mới 100%

Xin liên hệ

CLASS 125 BRASS GATE VALVEScrewed bonnet, Non-rising stem,
Threaded ends to BS21 (JIS B0203) or NPT,
or solder joint ends

W.O.G. non-shock 1.38 MPa (200 psi), Saturated steam pressure 0.86 MPa (125 psi)

**Fig. FH***

- Threaded end to BS21 (JIS B0203)


Fig. AKFH

- Threaded end to ASME B1.20.1

**Fig. CFH**

- Solder joint ends to ASME B16.18

*Taper pipe threads for connection shall refer to JIS B0203 standards, while the length of useful threads and the positions of gauge planes are built on KITZ standard.

**Dimensions**

Nominal Size	inch	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	mm
L	35	38	42	47	50	60	63	72	82	92		
L1 Solder		37	45	60	70	77	86	104	115	127		
H	70	73	73	87	97	118	126	154	187	205		
H Solder		77	77	87	97	118	126	154	187	205		
D	50	50	50	55	60	70	80	90	100	115		

Materials

Parts	Material
Body	Brass
Bonnet	Brass
Stem	Dezincification Resistant Brass
Disc	Brass
Gland packing	Aramid Fibers Graphite

⚠ Solder joint end valves should not be used in service where the temperature of the line fluid is higher than the softening point of the solder.

⚠ Do not use for flammable gas or toxic gas.

CLASS 125 BRONZE GATE VALVEScrewed bonnet*, Non-rising stem,
Threaded ends to BS21 (JIS B0203) or NPT,
or solder joint ends

W.O.G. non-shock 1.38 MPa (200 psi), Saturated steam pressure 0.86 MPa (125 psi)

*Size 1/4 to 2: Screwed-over-bonnet

**Fig. H***

- Threaded end to BS21 (JIS B0203)


Fig. AKH

- Threaded end to ASME B1.20.1

**Fig. CH**

- Solder joint ends to ASME B16.18

*Taper pipe threads for connection shall refer to JIS B0203 standards, while the length of useful threads and the positions of gauge planes are built on KITZ standard. (size up to 2 and 4)

**Dimensions**

Nominal Size	inch	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	mm
L	42	45	50	57	61	67	74	90	100	121		
L1 Solder		39	46	61	72	78	87	102	115	130	173	
H	74	80	90	105	118	135	159	202	223	280		
D	50	50	55	60	70	80	90	115	135	155		

Materials

Parts	Material
Body	Bronze
Bonnet	Bronze
Stem	Dezincification Resistant Brass
Disc	Dezincification Resistant Brass/Bronze*
Gland packing	Aramid Fibers Graphite

*Size 1/4 & larger

⚠ Solder joint end valves should not be used in service where the temperature of the line fluid is higher than the softening point of the solder.

⚠ Do not use for flammable gas or toxic gas.

CLASS 125 BRONZE GATE VALVEScrewed bonnet, Non-rising stem,
Threaded ends to BS21 (JIS B0203)

W.O.G. non-shock 1.38 MPa (200 psi), Saturated steam pressure 0.86 MPa (125 psi)

**Fig. S***

- Threaded end to BS21 (JIS B0203)

*Taper pipe threads for connection shall refer to JIS B0203 standards, while the length of useful threads and the positions of gauge planes are built on KITZ standard.

**Dimensions**

Nominal Size	inch	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	mm
L	38	42	47	50	60	63	72	80	90		
H	75	75	86	97	117	126	154	167	200		
D	50	50	55	60	70	80	90	100	115		

Materials

Parts	Material
Body	Bronze
Bonnet	Brass
Stem	Dezincification Resistant Brass
Disc	Brass
Gland packing	Aramid Fibers Graphite

⚠ Do not use for flammable gas or toxic gas.

Sản phẩm khác



—

[VAN BƯỚC KITZ G-PN10ZJUE](#)

[Xem thêm VAN BƯỚC KITZ G-PN10ZJUE](#)



—

[VAN BƯỚC KITZ PN10ZJUE](#)

[Xem thêm VAN BUỒM KITZ PN10ZJUE](#)



—

[VAN 1 CHIỀU KITZ 10SFBF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SFBF](#)



—

[VAN 1 CHIỀU KITZ 10SF](#)

[Xem thêm VAN 1 CHIỀU KITZ 10SE](#)



—

[VAN 1 CHIỀU KITZ 150SCOS](#)

[Xem thêm VAN 1 CHIỀU KITZ 150SCOS](#)



—

[VAN BI KITZ 150SCTDZ](#)

[Xem thêm VAN BI KITZ 150SCTDZ](#)

